
Revisions				
Issue Date	Note			DATASHEET
1 14/04/2022	See note GTXPDC/486			
1. Mechanical				
Fixing Method		Not applicable		
Durability		500 mating cycles		
2. Environme	ntal			
RoHS Comp	liant	Yes	32.50	
Temperature	e Range	-55 to +85 degrees C		

3. Electrical

Dielectric Withstanding Impedance Interface Frequency Working Voltage 1500 Volts RMS Maximum 75 ohms 1 GHz 500 Volts RMS Maximum

27.40 Ref



							Author	РЈР		
				Unless otherwise specified tolerances		• • •	Drawn by	РЈР		
				0.5-5 = ±0.2 >5-30 = ±0.4	עות∧זלבאונ//	Drawing date	14/04/2022			
				>30-120 = ±0.6 >120-315 = ±1.0			Checked by	DB		
Ļ	Dielectric	Delrin	White	>315-1000 = ±1.6 Angles = ±5°		Checked date	20/04/2022			
3	Pin	Brass	Gold	Units = mm			Scale	Not to scale		
2	Contact	Brass	Gold	This document is the confidential	Part Number	BN10-1510-A06-1	406-1			
	Body	Brass	Nickel	property of Gigatronix Limited and may not be copied, reproduced or transmitted to any third party	Title: BNC Jac	to Plug to Jack Adaptor, Nickel Plated, 75 ohms				
	Description	Material	Finish	without written authorisation.						