# **DATASHEET**

# Revisions Issue Date Note 1 06/06/2022 See GTXPDC/525

#### 1. Mechanical

Cable Retention Equal to breaking strain of cable

Yes

Durability 500 mating cycles

Fixing Method Crimp

#### 2. Environmental

RoHS Compliant

Temperature Range -55 to +85 degrees C

#### 3. Electrical

Dielectric Withstanding 1500 Volts RMS Maximum

Impedance 75 ohms

Interface Frequency 1 GHz

Working Voltage 500 Volts RMS Maximum



	Description	Material	Finish	
1	Body	Brass	Nickel	
2	Coupling Nut	Zinc Alloy	Nickel	
3	Pin	Brass	Gold	
4	Ferrule	Brass	Nickel	
5	Dielectric	Delrin	White	
6	Insulator	Delrin	White	

Unless otherwise specified tolerances  $0.5\text{-}5 = \pm 0.2$   $> 5\text{-}30 = \pm 0.4$   $> 30\text{-}120 = \pm 0.6$   $> 120\text{-}315 = \pm 1.0$   $> 315\text{-}1000 = \pm 1.6$  Angles =  $\pm 5^\circ$  Units = mm

This document is the confidential property of Gigatronix Limited and may not be copied, reproduced or transmitted to any third party without written authorisation.



Author	РЈР	
Drawn by	РЈР	
Drawing date	06/06/2022	
Checked by	DB	
Checked date	29/06/2022	
Scale	Not to scale	

Part Number

BN15-0179-C06-1

Title: BNC Crimp Plug, Nickel Plated, RG179



## ASSEMBLY INSTRUCTIONS

### **Assembly Instructions:**

1) Slide the ferrule onto the cable and strip the cable to the dimensions as shown, taking care not to nick the centre conductor or braid







2) Open the cable braid and slide the insulator tube over the dielectric and under the braid. Crimp the pin onto the centre core and slide the pin into the body until it captivates, ensuring that the cable braid is on the outside of the connector mandril.

3) Slide the ferrule forward and crimp



Crimp Die Sizes:

5.41mm Hex., 1.69mm Hex

**Strip Dimensions:** 

A=12.00mm, B=3.0mm, C=3.0mm



	Dody		
1	Body	Brass	Nickel
2	Coupling Nut	Zinc Alloy	Nickel
3	Pin	Brass	Gold
4	Ferrule	Brass	Nickel
5	Dielectric	Delrin	White
6	Insulator	Delrin	White

5

Unless otherwise specified tolerances  $0.5-5 = \pm 0.2$   $>5-30 = \pm 0.4$   $>30-120 = \pm 0.6$   $>120-315 = \pm 1.0$   $>315-1000 = \pm 1.6$  Angles =  $\pm 5^{\circ}$  Units = mm

This document is the confidential property of Gigatronix Limited and may not be copied, reproduced or transmitted to any third party without written authorisation.



	Author	PJP
	Drawn by	РЈР
	Drawing date	06/06/2022
	Checked by	DB
	Checked date	29/06/2022
	Scale	Not to scale

Part Number

BN15-0179-C06-1

**Title**: BNC Crimp Plug, Nickel Plated, RG179