Revisions			
Issue Date		Note	
1	07/11/2023	See GTXPDC/860	

#### 1. Mechanical

27N Cable Retention

Durability 500 mating cycles

Fixing Method Solder Cable Retention 136N Maximum Panel Thickness 2.00mm

## 2. Environmental

RoHS Compliant Yes


Temperature Range -65 to +165 degrees C

### 3. Electrical

Dielectric Withstanding 750 Volts RMS Maximum


Impedance 50 ohms Interface Frequency 12.4 GHz

Working Voltage 335 Volts RMS Maximum





**DATASHEET** 



6	Lock Nut	Brass	Gold
5	Washer	Brass	Gold
4	O Ring	Silicone	Red
3	Dielectric	PTFE	White
2	Pin	Brass	Gold
1	Body	Brass	Gold
	Description	Material	Finish

Unless otherwise specified tolerances  $0.5-5 = \pm 0.2$  $5-30 = \pm 0.4$ >30-120 = ±0.6 >120-315 = ±1.0 >315-1000 = ±1.6 Angles = ±5° Units = mm


This document is the confidential property of Gigatronix Limited and may not be copied, reproduced or transmitted to any third party without written authorisation.



Author	РЈР
Drawn by	РЈР
Drawing date	07/11/2023
Checked by	DB
Checked date	07/11/2023
Scale	Not to scale

Part Number | MA02-0405-R01-R

Title: SMA Reverse Polarity Bulkhead Jack, Gold Plated, RG405, .085 semi-rigid



# **ASSEMBLY INSTRUCTIONS**

## **Assembly Instructions**

1) Strip the cable to the dimensions as shown, taking care not to nick the centre core.



2) Solder the pin onto the centre core, then screw the body fully into an SMA Jack Gauge. Slide the pin into the back of the body until it meets the gauge and solder the cable to the mandril.

3) Fit the insulator into the front of the body using an SMA Insertion Tool.



**Strip Dimensions:** A=0.0mm, B=2.2mm



		В

	Description	Material	Finish	
1	Body	Brass	Gold	aı
2	Pin	Brass	Gold	-
3	Dielectric	PTFE	White	
4	O Ring	Silicone	Red	
5	Washer	Brass	Gold	
6	Lock Nut	Brass	Gold	

Unless otherwise specified tolerances  $0.5-5 = \pm 0.2$  $>5-30 = \pm 0.4$  $30-120 = \pm 0.6$  $120-315 = \pm 1.0$  $315-1000 = \pm 1.6$ Angles = ±5° Units = mm

This document is the confidential property of Gigatronix Limited and may not be copied, reproduced or transmitted to any third party without written authorisation.



	Author	PJP
	Drawn by	РЈР
	Drawing date	07/11/2023
	Checked by	DB
	Checked date	07/11/2023
	Scale	Not to scale

Part Number | MA02-0405-R01-R

Title: SMA Reverse Polarity Bulkhead Jack, Gold Plated, RG405, .085 semi-rigid