Revisions				
Issue	Date	Note		
1	20/04/2023	See GTXPDC/714		

DATASHEET



Equal to breaking strain of cable

Durability 500 mating cycles

Fixing Method Crimp
Contact Terminaton Crimp



2. Environmental

RoHS Compliant Yes

Temperature Range 55 to +85 degrees C

3. Electrical

Dielectric Withstanding 1500 Volts RMS Maximum

Impedance 50 ohms
Interface Frequency 11 GHz

Working Voltage 500 Volts RMS Maximum



_	Bouy	,	
1	Body	Zinc Alloy	Nickel
2	Coupling Nut	Brass	Nickel
3	Pin	Brass	Gold
4	Dielectric	Delrin	White
5	Ferrule	Brass	Nickel

Unless otherwise specified tolerances $0.5\text{-}5 = \pm 0.2$ $> 5\text{-}30 = \pm 0.4$ $> 30\text{-}120\text{-}315 = \pm 1.0$ $> 315\text{-}1000 = \pm 1.6$ Angles = $\pm 5^\circ$ Units = mm

This document is the confidential property of Gigatronix Limited and may not be copied, reproduced or transmitted to any third party without written authorisation.



Author	РЈР
Drawn by	РЈР
Drawing date	20/04/2023
Checked by	DB
Checked date	24/04/2023
Scale	Not to scale

Part Number

TN15-L240-C06

Title: TNC Crimp Plug, Nickel Plated, LBC240



ASSEMBLY INSTRUCTIONS

Assembly Instructions:

1) Slide the ferrule onto the cable and strip the cable to the dimensions as shown, taking care not to nick the centre conductor or braid







2) Crimp the Contact onto the centre core and slide the Contact into the body until it captivates, ensuring that the cable braid is on the outside of the connector mandril

3) Slide the ferrule forward and crimp



Crimp Die Sizes:

6.48mm Hex., 1.69mm Hex

Strip Dimensions:

A=7.5mm, B=3.0mm, C=4.0mm



	Description	Material	Finish	
1	Body	Zinc Alloy	Nickel	
2	Coupling Nut	Brass	Nickel	
3	Pin	Brass	Gold	
4	Dielectric	Delrin	White	
5	Ferrule	Brass	Nickel	

Unless otherwise specified tolerances $0.5-5 = \pm 0.2$ $>5-30 = \pm 0.4$ $30-120 = \pm 0.6$ $120-315 = \pm 1.0$ $315-1000 = \pm 1.6$ Angles = ±5° Units = mm

This document is the confidential property of Gigatronix Limited and may not be copied, reproduced or transmitted to any third party without written authorisation.



Auth	or	PJP
Drav	vn by	РЈР
Drav	ving date	20/04/2023
Chec	ked by	DB
Chec	ked date	24/04/2023
Scale	е	Not to scale

Part Number TN15-L240-C06

Title: TNC Crimp Plug, Nickel Plated, LBC240